

QY80K FULL HYDRAULIC TRUCK CRANE

徐工集团 · 臂架机械

系统优化升级

QY80K

SYSTEMIC OPTIMIZATION & UPGRADE

最大起重能力 Max. Total Rated Lifting Load		80t
主臂最大起升高度 Full-extend Boom Lifting Height		44.8m
副臂最大起升高度 Full-extend Boom+Jib Lifting Height		60.8m



此样本所取的照片和技术参数,由于设计上的改进等原因,有可能与用户交货的产品不符,请予谅解,恕不另行通知。
All specifications are subject to technical modifications without notice.

徐工集团徐州重型机械有限公司

地址: 中国江苏徐州市铜山路165号
Add.No.165 Tongshan Road Xuzhou Jiangsu China
电话(Tel): 0516-83462242 83462350
传真(Fax): 0516-83461669
邮编(Post Code): 221004
网址(URL): <http://www.xzxx.com.cn>
E-mail: yx@xzxx.com.cn
服务电话(Service Tel): 0516-83461183
服务传真(Service Fax): 0516-83461180
质量监督电话(Quality Inquiry Tel): 0516-87888268
备件电话(Spare Parts Tel): 0516-83461542
大修厂(Overhaul Factory): 0516-83461904



3C强制性产品认证证书 职业健康安全管理体系认证证书 环境管理体系认证证书



--- 第一版企业证书 ISO9001质量管理体系证书 ISO14001环境管理体系证书

2004年11月版

The Series of Construction Crane

- 全地面起重机 汽车起重机 履带式起重机
- All-Terrain Crane Series Truck Crane Series Crawler Crane Series

徐州重型机械有限公司

QY80K 汽车起重机

QY80K TRUCK CRANE

徐工重型QY80K采用五轴单发动机设计,底盘通过能力强;双功控模式的电控发动机,环保且高效;采用圆弧形截面吊臂,中长臂性能尤其令人瞩目。固定平衡重和自拆装平衡重组合、2级水平支腿,大幅度拓展了整机的起重性能;整机秉承徐工重型K系列产品的特点,各部件组合紧凑、布局合理、美观且更人性化。

QY80K is designed as 5-axle crane carrier with single engine, and the chassis has strong pass-ability. The engine is electronic-controlled injection engine with two operation control modes, environmental protection and high efficient. The oviform boom profile contributes prominent lifting performance for half and fully extended boom section. The combination of fixed counterweight and self-assembled counterweight and 2-section outrigger increase the crane overall lifting performance. The whole machine still holds the K series crane features, compact arrangement for each part, reasonable layout, good-looking appearance and ergonomically design.



集K系列起重机新技术、新工艺于一身

Combination of New Technology and New Techniques of K Series Crane



液压系统为高效节能的恒功率变量系统
The hydraulic system is constant output variable displacement system, high work efficient and energy saving.



配有自动润滑装置
Centralized lubrication system



采用双功控模式的电控发动机,行驶时输出315kW功率,上车作业时仅输出180 kW
The electronic-controlled injection engine with two operation control modes, 315kW output for crane travel drive and only 180 kW output for crane lifting operation.

采用第三代改良型操纵室-驾驶室,空间利用更加合理,流线型的外观造型风格统一,与徐工重型独有的圆弧形吊臂相呼应。(可选配三色灯)
The third generation of improved type operator's cab and driver's cab, interior space is more reasonable, streamlined appearance and unified style, and with our exclusive oviform boom profile. (three-color lamp is for option)



各种机构和控制系统的部件精确到每个匹配细节
Various mechanism and control system are accurate to every detail.




通过性能卓越的五轴底盘
The 5-axle crane carrier has excellent passability



精巧的高悬式弧形配重
The smart and highly suspended arc type counterweight.



整体感更强,整车品质感更优越
The overall sense is stronger, and the overall quality is superior.



平衡重为自装组合式,有3种组合方式
The counterweight is self-assembly and with 3 type of combination.



人性化的体贴设计,造型美观,具有良好的隔音效果
The ergonomically and considerate design, beautiful shape and with good soundproof effect.